

APPLICATION

Belt for work positioning.

This product is not designed for use as a fall arrest device



Component & characteristic

- Side anchoring: 2 « D » rings.
- Quick adjustable and opening with flat buckles.
- Foam belt lightweight and rot-proof.
- Double thickness foam belt support with closed cells blue exterior, black knitted material inside.
- Buckles: zinged steel
- PES belt, dried thread, width: 44 mm, black,
- Automatic stitching: PES thread

Model

- CE01 S : Small
- CE01 M : Medium
- CE01 XL : Large

Size / Weight / Code

- | | | |
|-----------------|----------|-------------|
| ▪ CE01 S 44-46 | 0,420 Kg | code 032882 |
| ▪ CE01 M 48-50 | 0.450 Kg | code 010052 |
| ▪ CE01 XL 52-54 | 0.480 Kg | code 010062 |

Description

Working belt incorporating side « D » for attaching a work positioning lanyard.

Adjustable with quick opening using a single set of buckles. Excess belt is held in position with plastic loops.

The back support is made of thermoformed foam.

The inside surface has a sponge type covering.

There are 3 buckles for attaching a tool bag.

This working belt may be combined with any harness of our range, using belt loops making a fully integrated belt-harness assembly.

CE certification

- n° 0082/352/160/05/97/0087
- Notified body : APAVE (N°0082)

Standard

- EN358